



## DS3-S

### The most powerful Dual Microinverter

- One microinverter connects to two modules
- Max output power reaching 600VA
- Two input channels with independent MPPT
- Reactive Power Control
- Maximum reliability, IP67
- Encrypted Zigbee Communication
- Safety protection relay integrated


## PRODUCT FEATURES

As part of its 3<sup>rd</sup> generation of microinverters, APsystems is releasing the DS3-S, a customized microinverter with a power of 600VA in order to accommodate your special projects requiring lower power (i.e: balcony systems). With 2 independent MPPTs, encrypted Zigbee signals, the DS3-S benefit from an entirely new architecture and are fully backwards compatible with the QS1 and YC600 microinverters.

The innovative and compact design make the product lighter while maximizing power production. The components are encapsulated with silicone to reduce stress on the electronics, facilitate thermal dissipation, enhance waterproof properties, and ensure maximum reliability of the system via rigorous testing methods including accelerated life testing. A 24/7 energy access through Apps or web based portal facilitate remote diagnosis and maintenance.

The DS3-S is interactive with power grids through a feature referred to as RPC (Reactive Power Control) to better manage photovoltaic power spikes in the grid. With a performance and an efficiency of 97%, a unique integration with 20% less components, APsystems DS3-S are a game changer to residential and commercial PV.

## WIRING SCHEMATIC



## Datasheet | DS3-S Microinverter

### Model

DS3-S

### Input Data (DC)

Recommended PV Module Power (STC) Range	250Wp-450Wp+
Peak Power Tracking Voltage	25V-55V
Operating Voltage Range	16V-60V
Maximum Input Voltage	60V
Maximum Input Current	18A x 2

### Output Data (AC)

Maximum Continuous Output Power	600VA
Nominal Output Voltage/Range*	230V/184V-253V
Nominal Output Current	2.6A
Nominal Output Frequency/ Range*	50Hz/48Hz-51Hz
Power Factor(Default/Adjustable)	0.99/0.8 leading...0.8 lagging
Maximum Units per 20A Branch**	7

### Efficiency

Peak Efficiency	97%
CEC Efficiency	96.5%
Nominal MPPT Efficiency	99.5%
Night Power Consumption	20mW

### Mechanical Data

Operating Ambient Temperature Range	- 40 °C to + 65 °C
Storage Temperature Range	- 40 °C to + 85 °C
Dimensions (W x H x D)	262mm x 218mm x 41.2mm
Weight	2.6kg
AC Bus Cable	2.5mm <sup>2</sup>
DC Connector Type	MC4
Cooling	Natural Convection - No Fans
Enclosure Environmental Rating	IP67

### Features

Communication (Inverter To ECU)	Encrypted ZigBee
Isolation Design	High Frequency Transformers, Galvanically Isolated
Energy Management	Energy Management Analysis (EMA) system
Warranty***	10 Years Standard ; 20 Years Optional

### Compliances

Safety, EMC & Grid Compliances	EN 62109-1; EN 62109-2; EN 61000-6-1; EN 61000-6-3; VDE-AR-N 4105
--------------------------------	---

\*Nominal voltage/frequency range can be extended beyond nominal if required by the utility.

\*\*Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

\*\*\* To be eligible for the warranty, APsystems microinverters need to be monitored via the EMA portal. Please refer to our warranty T&Cs available on [emea.APsystems.com](http://emea.APsystems.com).

### European offices

#### APsystems

Cypresbaan 7, 2908LT, Capelle aan den IJssel, The Netherlands

Tel : 031-10-2582670

Email : [emea@apsystems.com](mailto:emea@apsystems.com)



© All Rights Reserved

Specifications subject to change without notice please ensure you are using the most recent update found at web : [emea.APsystems.com](http://emea.APsystems.com)

#### APsystems

Rue des Monts d'Or, ZAC de Folliouses Sud-Les Echets,

01700 Miribel, France

Email : [emea@apsystems.com](mailto:emea@apsystems.com) | Tel: +33-4-81 65 60 40